according to Regulation (EC) No 1907/2006

Tint Remover

Revision date: 27.02.2018 Product code: 658. Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Tint Remover

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture Professional: Cosmetics

Uses advised against

none

1.3. Details of the supplier of the safety data sheet

Company name: Biosmetics GmbH Street: Ziegeleiweg 40 Place: D Goldberg

Telephone: +49 [0] 451 | 30 800 90 Telefax: +49 [0] 451 | 20 351 03

Responsible Department: Dr. Gans-Eichler e-mail: info@tge-consult.de Chemieberatung GmbH rel.: +49(0)251/394868-69

Raesfeldstr. 22 www.tge-consult.de D-48149 Münster

1.4. Emergency telephone Tel.: +49 (0) 170 2450126

number:

Further Information

This product is subject to the cosmetic regulation. This sheet was prepared on a voluntary basis.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Serious eye damage/eye irritation: Eye Irrit. 2

Hazard Statements:

Flammable liquid and vapour. Causes serious eye irritation.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Warning

Pictograms:





Hazard statements

H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

according to Regulation (EC) No 1907/2006

	Tint Remover	
Revision date: 27.02.2018	Product code: 658.	Page 2 of 12

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to in accordance with official regulations.

Special labelling of certain mixtures

EUH208 Contains benzylsalicylate. May produce an allergic reaction.

Additional advice on labelling

Labelling according to cosmetic directive.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	nemical name			
	EC No	Index No REACH No			
	Classification according to Regulati	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			10 - < 15 %	
	200-661-7 603-117-00-0 01-2119457558-25				
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336				
118-58-1	benzylsalicylate			< 0.1 %	
	204-262-9				
	Skin Sens. 1A, Aquatic Chronic 2; H317 H411				

Full text of H and EUH statements: see section 16.

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

Take off immediately all contaminated clothing. Wash with plenty of water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

according to Regulation (EC) No 1907/2006

Tint Remover

Revision date: 27.02.2018 Product code: 658. Page 3 of 12

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. alcohol resistant foam.

In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO2). Sulphur oxides

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area.

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes.

Wear personal protection equipment. (See section 8.)

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations.

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Further information on handling

General protection and hygiene measures: See section 8.

according to Regulation (EC) No 1907/2006

Tint Remover

Revision date: 27.02.2018 Product code: 658. Page 4 of 12

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.

Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Advice on storage compatibility

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity.

Protect against: UV-radiation/sunlight. heat. moisture. frost.

storage temperature: 15-25 °C

7.3. Specific end use(s)

Cosmetics

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

	CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
ſ	67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
l			500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Worker DNEL,	long-term	dermal	systemic	888 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	500 mg/m³
Consumer DNE	EL, long-term	dermal	systemic	319 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	systemic	89 mg/m³
Consumer DNE	EL, long-term	oral	systemic	26 mg/kg bw/day

PNEC values

04011			
CAS No	Substance		
Environmen	Environmental compartment		
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
Freshwater		140,9 mg/l	
Freshwater	intermittent releases)	140,9 mg/l	
Marine wate	T.	140,9 mg/l	
Freshwater	ediment	552 mg/kg	
Secondary p	oisoning	160 mg/kg	
Micro-organ	sms in sewage treatment plants (STP)	2251 mg/l	
Soil		28 mg/kg	

according to Regulation (EC) No 1907/2006

Tint Remover

Revision date: 27.02.2018 Product code: 658. Page 5 of 12

8.2. Exposure controls







Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Professional: Use only outdoors or in a well-ventilated area.

Protective and hygiene measures

The usual precautions for handling chemicals should be considered.

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing.

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible). DIN EN 166

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves. (DIN EN 374)

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time >= 480 min. penetration time (maximum wearing period): ~ 120 min. (estimated)

In the case of wanting to use the gloves again, clean them before taking off and air them well. Before using check leak tightness / impermeability.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

exceeding exposure limit values

Insufficient ventilation.

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: not determined
Odour: perfumed

pH-Value: not determined

Changes in the physical state

according to Regulation (EC) No 1907/2006

	Tint Remover	
Revision date: 27.02.2018	Product code: 658.	Page 6 of 12
Melting point: Initial boiling point and boiling range:	not applicable not determined	
Flash point:	~42 °C	
Explosive properties In use, may form flammable/explosive vapo	pur-air mixture.	
Lower explosion limits:	2 (IPA) vol. %	
Upper explosion limits:	12 (IPA) vol. %	
Ignition temperature:	425 (IPA) °C	
Decomposition temperature:	not determined	
Oxidizing properties none.		
Vapour pressure: (at 20 °C)	48 (IPA) hPa	
Density:	not determined	
Water solubility:	miscible.	
Solubility in other solvents not determined		
Viscosity / dynamic: (at 20 °C)	not determined	
Viscosity / kinematic: (at 20 °C)	not determined	
Vapour density:	not determined	
Evaporation rate:	not determined	
Solvent separation test:	not determined	
Solvent content:	not determined	

not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

9.2. Other information
Solid content:

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Protect against: UV-radiation/sunlight. heat. moisture. In use may form flammable/explosive vapour-air mixture.

Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis.

10.6. Hazardous decomposition products

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide Carbon dioxide (CO2). Sulphur oxides

SECTION 11: Toxicological information

according to Regulation (EC) No 1907/2006

Tint Remover

Revision date: 27.02.2018 Product code: 658. Page 7 of 12

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

The product has not been tested.

CAS No	Chemical name	Chemical name					
	Exposure route	Dose		Species	Source	Method	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol						
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier		
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier		
	inhalative vapour	LC50 mg/l	(>25)	Rat (6h)	MSDS external		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

May cause sensitisation especially in sensitive humans.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

propan-2-ol; isopropyl alcohol; isopropanol:

OECD Guideline 471 (Bacterial Reverse Mutation Assay) = negative., AllgK267153: ECHA Dossier; OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) = negative., Literature information: ECHA Dossier; No indications of human carcinogenicity exist., Literature information: ECHA Dossier; Reproductive toxicity: Method: OECD Guideline 415 (One-Generation Reproduction Toxicity Study); Species: Rat; Result: NOAEL = 853 mg/kg; Literature information: ECHA Dossier; Developmental toxicity/teratogenicity: Method: (oral.) OECD

Guideline 414 (Prenatal Developmental Toxicity Study); Species: Rabbit; Result: NOAEL = 480 mg/kg;

Literature information: ECHA Dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

propan-2-ol; isopropyl alcohol; isopropanol:

Chronic inhalative toxicity (Rat): NOAEC = 5000 ppm (OECD 451), Literature information: ECHA Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available.

Further information

Solvent:

Symptoms: Depression of the central nervous system. Liver and kidney damage. drowsiness. vomiting. Nausea. Dizziness. unconsciousness. Impaired consciousness. Intoxication. erythema (redness)

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested.

according to Regulation (EC) No 1907/2006

Tint Remover Revision date: 27.02.2018 Product code: 658. Page 8 of 12

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alc	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas	ECHA Dossier	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	>1800		Scenedesmus quadricauda	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	>10000	48 h	Daphnia magna (24h)	ECHA Dossier	OECD Guideline 202
118-58-1	benzylsalicylate						
	Acute fish toxicity	LC50 mg/l	1,06	96 h	Danio rerio	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	1,29	72 h	Pseudokirchnerella subcapitata	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	1,13	48 h	Daphnia magna	ECHA Dossier	

12.2. Persistence and degradability

The product has not been tested.

	The product has not seen tested.				
hemical name					
Method Value d Source					
Evaluation					
propan-2-ol; isopropyl alcohol; isopropanol					
EU Method C.5/ EU Method C.6 53% 5 ECHA Dossier					
Easily biodegradable (concerning to the criteria of the OECD)					
benzylsalicylate					
OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D 93% 28 ECHA Dossier					
Easily biodegradable (concerning to the criteria of the OECD)					
	Evaluation propan-2-ol; isopropyl alcohol; isopropanol EU Method C.5/ EU Method C.6 Easily biodegradable (concerning to the criteria of the OECD) benzylsalicylate OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	Method Value Evaluation propan-2-ol; isopropyl alcohol; isopropanol EU Method C.5/ EU Method C.6 Easily biodegradable (concerning to the criteria of the OECD) benzylsalicylate OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D 93%	Method Value d Evaluation propan-2-ol; isopropyl alcohol; isopropanol EU Method C.5/ EU Method C.6 53% 5 Easily biodegradable (concerning to the criteria of the OECD) benzylsalicylate OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D 93% 28		

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process. Control report for waste code/ waste marking according to EAKV:

according to Regulation (EC) No 1907/2006

Tint Remover

Revision date: 27.02.2018 Product code: 658. Page 9 of 12

Waste disposal number of waste from residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused

products; organic wastes containing hazardous substances; hazardous waste

Waste disposal number of used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused

products; organic wastes containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

50110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol.)

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1
Special Provisions: 274 601
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol.)

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1
Special Provisions: 274 601
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol.)

14.3. Transport hazard class(es): 3
14.4. Packing group: III

according to Regulation (EC) No 1907/2006

Tint Remover

Revision date: 27.02.2018 Product code: 658. Page 10 of 12

Hazard label: 3



Special Provisions: 223, 274, 955

Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1993

14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol.)

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

See section 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): not determined 2004/42/EC (VOC): not determined

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): 3

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

according to Regulation (EC) No 1907/2006

	Tint Remover	
Revision date: 27.02.2018	Product code: 658.	Page 11 of 12

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

SECTION 16: Other information

Changes

Rev. 1.00; 27.02.2018, Initial release

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

CAS Chemical Abstracts Service

DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level

NTP: National Toxicology Program

N/A: not applicable

OSHA: Occupational Safety and Health Administration

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

SARA: Superfund Amendments and Reauthorization Act

SVHC: substance of very high concern

TRGS Technische Regeln fuerGefahrstoffe

TSCA: Toxic Substances Control Act

VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefaehrdender Stoffe

WGK: Wassergefaehrdungsklasse

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Eye Irrit. 2; H319	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

EUH208 Contains benzylsalicylate. May produce an allergic reaction.

Further Information

Classification according EC regulation 1272/2008 (CLP): - Classification procedure:

according to Regulation (EC) No 1907/2006

Tint Remover

Revision date: 27.02.2018 Product code: 658. Page 12 of 12

Health hazards: Calculation method. Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)